



Automatic Transfer Switch




This product is designed with two inputs powered by two independent power sources. If the first one fails, the second one takes over automatically. After the transition to the secondary power source, the ATS can also return to the primary when power is restored.

- ATS is dedicated to UPS from 1 to 3 kVA.**
 - Convenient and user-friendly 19" solution (1U) to fit into diverse working environment
- 2 independant power sources**
 - Preferred source selection on front panel
 - Dual power supply for redundancy
 - Povides seamless powerswitch for IT equipments
- USB & RS 232 communication ports / Dry Contact port**
 - Built-in USB and RS232 communications

CONNECTION

- Dry contact port
- Output receptacles "Output 1" (IEC 10A)
- Output receptacles "Output 2" (IEC 10A)
- Output receptacles "Output 3" (IEC 16A)
- Input source A connector
- Input source B connector



TECHNICAL CHARACTERISTICS

ATS

| INPUT | |
|---------------------------------------|--|
| Input Voltage | 220/230/240 VAC |
| Acceptable Voltage Range | 180 - 258 VAC |
| Input Fréquency | 50 or 60 Hz |
| Maximum input current | 16 A |
| Input connectors | 2 x IEC-C20 |
| OUTPUT | |
| Output voltage | 220/230/240 VAC |
| Maximum output current | 10 A for IEC-C13 outlets / 16 A for IEC-C19 outlet |
| Output receptacles | 8 x IEC-C13 / 1 x IEC-C19 |
| MANAGEMENT | |
| Ports de communication | USB / RS232 |
| Temps de transfert | 9-12ms (Typical), 16ms max. |
| PHYSICAL CHARACTERISTICS | |
| Dimensions D x W x H (mm) | 330 x 483 x 44 (1U) |
| Net weight (kg) | 5 |
| Net weight including accessories (kg) | 8 |
| ENVIRONNEMENT | |
| Humidity | 0-95% Relative Humidity @ 0-40° non-condensation |
| NORMES | |
| Standard | CE RoHS |
| Electromagnétic compatibility (EMC) | EN62040-2:2006 / EN 61000-4-2:2009 / EN 61000-4-3:2006+A1:2008+A2:2010 / EN 61000-4-4:2004 + A1:2010 / EN 61000-4-5:2006 / EN 61000-2-2:2002 |
| Low voltage (LVD) | EN 60950-1: 2006 / EN 60040-1: 2008 |
| SALES INFO | |
| Warranty | 2 years |
| PN | 61453 |



19" rack-ready version



IEC output



USB & RS232 communication port



Infosec Communication

15, Rue du Moulin
44880 SAUTRON - FRANCE

Sales Contact

Tél : 02 40 76 11 77
sales@infosec.fr